VALCO 4T PRIMO

Engine oil SAE 50

Engine oil for passenger cars and light commercial vehicles.

VALCO 4T PRIMO will ensure internal cleanliness of engine as well as protection against wear.

This oil is recommended when API SF / CF performance level is required.

Specifications

- ✓ Specs

Physicochemical Characteristics

Characteristics	Method	Unit	Typical value	Min.	Max.
Viscosity grade	SAE J300	-	50	-	-
Kinematic viscosity @ 100°C	ASTM D 7042	cSt	17.6	16.3	21.9
Kinematic viscosity @ 40°C	ASTM D 7042	cSt	192	-	-
Viscosity index	ASTM D 2270	-	99	-	-
HTHS viscosity @ 150°C	ASTM D 4683	mPa.s	4.8	3.7	-
Density @ 20°C	ASTM D 7042	-	0.886	-	-
Pour point	ASTM D 97	°C	-28	-	-
T.B.N.	ASTM D 2896	mg KOH/g	4.9	4.0	6.4
Spectrometric analysis	ICP	ppm			
Phosphorus			600	-	-
Zinc			620	-	-
Calcium			1300	-	-
Molybdenum			60	-	-
NOACK volatility	ASTM D 5800	% mass	7.4	-	13.0
Colour	ASTM D 1500	-	3.5	-	6.0

Security

See Safety Data Sheet