VALCO 4 TEMPS MOTO 15W50

Motorcycle semi-synthetic engine oil 15W50

Top-of-the-range semi-synthetic oil for 4-stroke engines specially designed for motorcycle engines with engine, gearbox and clutch in common crankcase.

The friction of this oil is particularly studied for multi-disc clutches in oil bath.

Specifications

- ✓ API SL
- ✓ JASO MA2

Physicochemical Characteristics

Characteristics	Method	Unit	Typical value	Mini	Maxi
Viscosity grade	SAE-J	-	15W50	-	-
Kinematic viscosity @ 100°C	ASTM D 7279	cSt	17.5	16.3	21.9
Viscosity index	ASTM D 2270	-	155	-	-
CCS viscosity @ -25°C	ASTM D 5293	mPa.s	6000	-	7000
HTHS viscosity @ 150°C	CEC-L-36-A-97	mPa.s	4.1	3.5	-
Density	D 20/4	-	0.870	-	-
Pour point	ASTM D 5950	°C	-33	-	-
T.B.N.	ASTM D 2896	mg KOH/g	6.5	5.5	7.5
Sulfated ash	ISO/FDIS 3987	% masse	-	-	1.2
Spectrometric analysis Phosphorus Zinc Calcium	ICP	ppm	 870 900 1730	± 20 %	
NOACK volatility	ASTM D 5800	% masse	10	-	10
Colour	ASTM D1500	-	4.0	3.0	4.0

Security

See Safety Data Sheet