VALCO G-PROTECT UTM 75W-80

Mechanical transmission fluid 75W-80

Top of the range 75W-80 universal fluid for mechanical transmissions.

Its formula has been specially studied to prevent wear of gears and bearings even at low temperatures. VALCO G-PROTECT UTM 75W-80 is particularly suitable for the mechanical transmissions of European and Asian vehicles.

Important: this fluid is not suitable when API GL-5 performance level is required.

Specifications

- ✓ API GL-4+

VALCO G-PROTECT UTM 75W-80 is dedicated to mechanical transmissions of many manufacturers when a 75W-80 grade fluid is recommended (see list on the next page).

Physicochemical Characteristics

Characteristics	Method	Unit	Typical value	Min.	Max.
Viscosity grade	SAE J306	-	75W-80	-	-
Kinematic viscosity @ 100°C	ASTM D 7042	cSt	10.2	9.5	11.0
Kinematic viscosity @ 40°C	ASTM D 7042	cSt	62	-	-
Viscosity index	ASTM D 2270	-	154	145	-
Density @ 20°C	ASTM D 7042	-	0.862	-	-
Pour point	ASTM D 97	°C	-46	-	-
Brookfield viscosity @ -40°C	ASTM D 2896	cP	90000	-	150000
Spectrometric analysis	ICP	ppm			
Phosphorus			450	-	-
Calcium			3000	-	-
Sulfur			4150	-	-
Colour	ASTM D 1500	-	2.0	-	3.0

Security

See Safety Data Sheet

Specifications
API GL-4
BMW MTF LT-2
FIAT MZ6
FORD M2C186-A
GM 1940764
GM 1940768
NISSAN MT-XZ
NISSAN MT-XZ TL (JR Type)
PSA B71 2330 (EZL 848)
PSA B71 2315
PSA 9730 A8
SPECIAL GEAR OIL, MTF 94
SPECIAL HONDA MTF
SPECIAL HONDA MTF-II
HONDA MTF-III
TRANSELF NFJ, NFP, TRJ, TRT, TRZ, TRP, TRX
VOLVO 97308
VOLVO 97309
VW G 009 317