VALCO ATF VI

Automatic transmission fluid

Top of the range synthetic oil dedicated to multi-speed automatic transmissions (up to 9 speeds) and power steering of modern light and utility vehicles for which a low viscosity fluid is recommended.

VALCO ATF VI ensures excellent lubrication at low and high temperatures, anti-wear protection, resistance to oxidation and energy saving.

This fluid can be used for a large number of uses (see following page).

Specifications

This fluid meets requirements of Dexron® VI specification and is suitable for use for many manufacturers performance level (see the list on the following page).

Physicochemical Characteristics

Characteristics	Method	Unit	Typical value	Min.	Max.
Kinematic viscosity @ 100°C	ASTM D 7042	cSt	6.0	5.8	6.1
Kinematic viscosity @ 40°C	ASTM D 7042	cSt	28	-	-
Viscosity index	ASTM D 2270	-	165	145	-
Density @ 20°C	ASTM D 7042	-	0.837	-	-
Pour point	ASTM D 97	°C	-46	-	-40
Brookfield viscosity @ -20°C	ASTM D 2896	cP	860	-	1500
Brookfield viscosity @ -30°C	ASTM D 2896	cP	2400	-	5000
Brookfield viscosity @ -40°C	ASTM D 2896	cP	10300	-	20000
Flash point	ASTM D 92	°C	221	180	-
Colour	Visual	-	Red	-	-

Security

See Safety Data Sheet

OEM	Specifications
AISIN	AW-2
	JWS 3324 ATF, ATF-0WS
ATF	Shell 134
	Shell 3353
	Shell L12108
	Shell M-1375.4
	Shell M-1375.6
BENTLEY	P/N PY112995PA
BMW	ATF 3+
	ATF 7
	ATF 6
	M-L12108
	P/N 83 22 0 142 516
	P/N 83 22 0 397 114
	P/N 83 22 2 152 426
	P/N 83 22 2 163 514
	P/N 83 22 2 289 720
	P/N 83 22 2 305 397
	P/N 83 22 2 355 599
	P/N 83 22 2 413 477
FCA	8 & 9 Speed ATF, P/N 68218925AA/AB
	AW-1, P/N 68092912AA
	Dex-VI, P/N 68043742AA
	Fiat 9.55550-AV2
	Fiat 9.55550-AV5
	Fiat 9.55550-AV6
	P/N 05127382
	P/N 68157995AA/AB
	SP-4, P/N 68171866AA
	SP-IV, P/N 68171866AA
	SP-IV, P/N 68171869AA
FORD	P/N XT-10-QLV [LV]
	P/N XT-6-QSP [SP]
GM	AW-1, P/N 19256039
	Dex-VI [GMW 16444]
	P/N 1940773; 19 40 773
	WS, P/N 88863400 / 88863401
HONDA ACURA	ATF DW-1 P/N 08200-9008
	ATF Type 3.0 P/N 08200-9016-A
	ATF Type 3.1 P/N 08200-9017
HYUNDAI KIA	ATF SP-IV
	P/N 040000C90SG
	SPH-IV
	SP-IV
	SP-IV-RR
	WS, spec NWS-9638
ISUZU	ATF WSI
JAGUAR	02JDE 26444
	Fluid 8432

OEM	Specifications
JAMA	JASO M315, Class 1-A-LV
LAND ROVER	AW-1 P/N LR0022460: LV
	P/N TYK500050
	LR023288/023289
MASERATI	Oil No. 231603
MAZDA	ATF FZ
MERCEDES	MB 236.12
	MB 236.14
	MB 236.15
	MB 236.16
	MB 236.17
	MB 236.41
MITSUBISHI	ATF-J3
	Dia Queen ATF-MA1, P/N MZ320775
	Dia Queen ATF-PA, P/N 4030401
	SP-IV
NISSAN	Matic S, P/N 999MP-MTS00P
	Matic W
PEUGEOT	PSA 16 350 560 80
PORSCHE	P/N 000 043 304 00/01
SAAB	P/N 93 165 147
SUZUKI	Matic S
TOYOTA	ATF FZ
	JWS 3324, ATF WS (or NWS9638)
VW AUDI	G 052 533
	G 055 005 A2
	G 055 162 A2 or A6
	G 055 540 A2
	G 060 162 A2
ZF	LifeguardFluid 6 (ZF No. S671 090 255)
	LifeguardFluid 8 (ZF No. S671 090 312)
	LifeguardFluid 9 (ZF No. AA01.500.001)
	TE-ML 11A
	TE-ML 11B