VALCO POWER FLUID LDA

Power steering fluid

Polyvalent hydraulic fluid composed of high quality base oils and dedicated to multiple applications such as power steering systems, leveling sytems, hydraulic pneumatic spring systems, shock absorbing devices, hydrostatic driving gears, ABS/ASR and ASC systems, hydraulically controlled couplings and electro-hydraulic folding roof control systems.

Always refer to the manufacturer's recommendations before using the product.

Specifications

- ✓ ISO 7308
- ✓ DIN 51524-T3
- ✓ Chrysler MS-11655B
- ✓ DTFR 31B120
- ✓ EvoBus 39.060-001
- ✓ Ford WSS-M2C204-A
- ✓ MAN M 3289
- ✓ MB 345.0 / 345.1
- ✓ PSA S71 2710
- ✓ ZF TE-ML 02K (ZF004744)
- ✓ VW G 002 000 (TL 52146)
- ✓ Bentley JNV862564F
- ✓ BMW 81229407758 / 82111468041 / 83290429576
- ✓ Fendt X 902 011 622
- ✓ Iveco 18-1807 Classe APU
- ✓ Opel B 040 0070
- ✓ Porsche 000 043 203 33
- ✓ Saab 3032 380
- ✓ Volvo 1161529

Physicochemical Characteristics

Characteristics	Method	Unit	Typical value	Min.	Max.
Kinematic viscosity @ 100°C	ASTM D 7042	cSt	6.0	5.9	-
Kinematic viscosity @ 40°C	ASTM D 7042	cSt	18.7	18.0	19.5
Viscosity index	ASTM D 2270	-	313	-	-
Density @ 20°C	ASTM D 7042	-	0.830	-	-
Pour point	ASTM D 97	°C	-57	-	-50
Flash point	ASTM D 92	°C	154	145	-
Colour	Visual	-	Green	-	-

Security

See Safety Data Sheet