



Specification sheet: Transmatic ATF-U

Identification

Product code: HU0262

Revision index / date: B May 2016.

Features – properties

Red universal, fully synthetic, automatic transmission fluid to meet requirements of a majority of vehicle manufacturers.

Specifications

This fluid meets or exceeds performance requirements listed in back spreadsheet:

Physico-chemical characteristics

Characteristics	Method	Units	Typical	Mini	Maxi
Kinematic viscosity @ 40°C	ASTM D 445	cSt	31.0	-	-
Kinematic viscosity @ 100°C	ASTM D 445	cSt	6.3	6.1	6.7
Brookfield viscosity @ -40°C	-	cP	14000	-	17000
KRL	20h	cSt	5.7	5.4	-
Viscosity index	-	-	155	150	-
Poor point			-	-36	-
Density	D20/4	-	0.838	-	-
Colour	Visual	-	Red	-	-



Lubricants

Manufacturers	Specifications
Allison	C4
	TES-389
	TES-295
ATF	Esso LT 71141
	Shell 3353
	Shell 134
	JWS 3309
	Mobil ATF 3309
	Shell 3403-M115
	Shell M-1375.4
	Shell LA 2634
	Texaco ETL 7045E
	Texaco ETL 8072b
	Texaco N402
Bentley	P/N PY112995PA
BMW MINI	P/N 81 22 9 40 272/275
	P/N 81 22 9 407 858/859
	P/N 83 22 0 024 249/359
	P/N 83 22 0 026 922
	P/N 93 22 0 142 516
	P/N 83 22 0 397 114/163 514
	P/N 83 22 0 402 413
	P/N 83 22 0 403 248
	P/N 83 22 7 542 290
	P/N 83 22 9 407 765
	P/N 83 22 9 407 807
	P/N 83 22 2 152 426
	Chrysler Dodge Jeep
AS68RC ATF	
P/N 05127382AA	
P/N 68043742AA	
SP-III	
P/N 68157995AA	

Manufacturers	Specifications
Ford Lincoln/Mercury	P/N XT-10-QLV [LV]
	P/N XT-2-QDX [M]
	P/N XT-2-QSM [Syn]
	P/N XT-5-QM or -DM [V]
	P/N XT-6-QSP or -DSP [SP]
	P/N XT-8-QAW [Premium]
	P/N XT-9-QMM5 [FNR5]
	WSS-M2C922-A1
GM / GMC Opel / Saturn	AW-1
	Dexron® II/IIID/IIIE
	Dexron® III/IIIG/IIIH
	P/N 12378515 [Synthetic]
	P/N 19 40 700
	P/N 19 40 767
	P/N 21005966 Transaxle
	P/N 22717466
	P/N 88863400
	P/N 88863401
	P/N 88900925
P/N 9986195	
T-IV	
Type A Suffix A	
Honda Acura	DW-1
	Z-1
Hyundai/Kia	ATF Red-1K
	Genuine ATF
	JWS-3309 T-4
	NWS-9638 T-5
	P/N 040000C90SG
	P/N UM040 CH20 Red-1
SP-II/III	
SP-IV/SPH-IV	
Idemitsu	ATF HP
	K 17
Isuzu	ATF II/III
	Genuine ATF
	P/N 08200-9001



Lubricants

Manufacturers	Specifications
Jaguar	Fluid 0432
	JLM 20238
	JLM 20292
	JLM 21044
	K 17
	WSS-M2C922-A1
	Fluid 8432
JASO	M315, Class 1A
Land Rover	P/N TYK500050
	P/N LR0022460
	Esso Type LT 71141
	Texaco ETL-7045E
MAN	339A
Maserati	P/N 231603
Mazda	F-1
	FZ
	JWS 3317
	M-5, P/N XT-9-QMM5
	M-III
	Type T-IV
Mercedes Daimler	MB 236.3/5/6/7/8/9
	MB 236.10/11/91
	MB 236.12/14/15/41
Mitsubishi	ATF-J2
	ATF-J3
	SP, P/N MS991156
	SP-II/III
Nissan / Infinity	402
	Matic-D/J/K/W
	Matic-S
Porsche	P/N 000 043 204 41
	P/N 000 043 205 09
	P/N 000 043 205 28
	P/N 000 043 304 00
	P/N 999 917 547 00 (A2)
PSA Peugeot-Citroën	P/N 000169756
Renault	Matic D2

Manufacturers	Specifications
Saab	3309 -T- IV
	P/N 93 165 147 - AW-1
SSANG YONG	DSIH 5M-66
Subaru	HP
	P/N K0140Y0700
Suzuki	3314/3317
Toyota / Lexus Scion	Type D-II/T/T-III/T-IV
	Type WS
Volkswagen Audi	G 052 025 A2
	G 052 055
	G 052 162 (-A1-A2)
	G 052 533
	G 052 990 (A2)
	G 055 005 (-A,-A2)
	G 055 025 (A2)
	G 055 540 (A2)
	G US 000 162
G 055 162 (-A2, -A6)	
Volvo	G 060162 (-A1, -A2, -A6)
	P/N 1161521
Volvo Constr.Equip.(VCE)	P/N 1161540 / 1161640
	1273.41