



## Specification sheet: UTTO Transmission Oil

### Identification

Product code: HU0305

Revision index / date: K October 2019.

### Features – properties

Universal Transmission Tractor Oil dedicated to public works and agricultural appliances fitted with joint oil pan including wet brakes.

### Specifications

John Deere J20C / D  
Massey Ferguson CMS 1135 – 1143 – 1145  
Ford ESN-M2C-86C – ESN-M2C-134D  
Allison C4  
CASE MS1207, 1209  
CNH MAT 3525 (FNHA-201.00= M2C 134D) – MAT 3526 (FNHA 2-C-200.00)  
New Holland 410B  
API GL4+  
Caterpillar TO-2

### Physico-chemical characteristics

Characteristics	Method	Units	Typical	Mini	Maxi
Viscosity grade	SAE J	-	10W30	-	-
Kinematic viscosity @ 100°C	ASTM D7279	cSt	11.1	9.6	12.2
Kinematic viscosity @ 40°C	ASTM D7279	cSt	62.0	-	-
Brookfield @ -18°C	-	mPa.s	3500	-	4000
Brookfield @ -35°C	-	mPa.s	63900	-	70000
Pour point	ASTM D5950	°C	-	-	-
Density	D20/4	-	0.875	-	-
Colour	ASTM D1500	-	4.0	-	5.0
TBN	ASTM D 2896	mgKOH/g	10,6	9,6	11,6